





Slewing Drive Performance Parameters	
Rated Output Speed	1.2 rpm
Output Torque	15 kN.m
Tilting Moment	203 kN.m
Holding Torque	105,8 kN.m
Static Axial Rating	1598 kN
Static Radial Rating	640 kN
Gear Ratio	125 : 1
Efficiency	40 %
Precision	≤ 0.15 °
Hydraulic motor Performance Parameters	
Pressure	9MPa
Flow	40L/min

Hydraulic Motor Performance Data


BMR250 [253.5 cm^3/rev.]

Flow(L/min)	Pressure (MPa) 5	7	9	10	12	14	16	Continue (max.) 17.5	intermittent (max.) 20
5	175 **17**	243 **16**	304 **14**	342 **12**	407 **10**				
10	178 **37**	246 **35**	310 **31**	344 **28**	409 **23**	465 **18**	525 **11**		
20	175 **75**	244 **73**	308 **72**	340 **70**	408 **66**	463 **58**	520 **53**	558 **50**	636 **42**
30	162 **114**	235 **111**	304 **108**	332 **106**	400 **100**	455 **92**	516 **83**	550 **77**	621 **65**
40	143 **154**	223 **152**	300 **150**	329 **147**	396 **143**	447 **132**	512 **120**	546 **110**	617 **90**
50	124 **193**	208 **190**	289 **187**	323 **174**	384 **168**	440 **160**	503 **149**	535 **140**	600 **116**
Continue (max.) 60	103 **233**	192 **230**	280 **227**	314 **224**	371 **218**	426 **205**	489 **190**	514 **181**	578 **155**
70	88 **273**	178 **270**	264 **267**	301 **263**	356 **252**	418 **242**	479 **226**	498 **209**	560 **173**
intermittent (max.) 75	62 **294**	165 **291**	256 **287**	288 **283**	347 **274**	412 **263**	474 **249**	486 **236**	542 **211**

Torque (N.m) 621
Speed (rpm) 65

MOMENT LOAD CHART

Axial Load & Tilting Moment



REV	DATE	REVISER	REVISER
DESIGNED BY	2024/5/14	Li Ming	www.coresundrive.com
CHECKED BY	2024/5/14	Rui Wang	Coresun Drive Equipment Changzhou Co., Ltd.
APPROVED BY	2024/5/14	Shane Zhang	

ALL PROPRIETARY RIGHTS IN THE SUBJECT MATTER HERE OF ARE RESERVED, AND NO PERMISSION IS GRANTED OR TO DISCLOSE REPRODUCE THIS PRINT IN WHOLE OR IN PART, ANY OF THE INFORMATION TO OTHERS.

WEIGHT	SCALE	Slewing Drive	
	1 : 4		
SIZE	A3	SC21-125-RH-250A	REV
SHEET	1 / 1		A

SYMBOLE ISO